

UTT 30 Clevis Hanger

Pipe Hangers

Function: Recommend for suspension of non-insulated stationary pipe line.

Size: 1/2" Thru 12"

Material: Carbon Steel

Finish: Black Painted or Galvanized



Size		A		B		C		D		E		T		L		RS		Max. Rec. Load	
in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	KN
1/2"	DN15	1.18	30	1.1	28	1/4"	M6	0.84	21.3	1.61	41	0.1	2.5	1.97	50	3/8"	M10	610	2.71
3/4"	DN20	1.38	35	1.18	30	1/4"	M6	1.05	26.7	2.01	51	0.1	2.5	2.17	55	3/8"	M10	610	2.71
1"	DN25	1.65	42	1.26	32	1/4"	M6	1.31	33.4	2.2	56	0.1	2.5	2.36	60	1/2"	M12	730	3.24
1-1/4"	DN32	2.01	51	1.57	40	1/4"	M6	1.66	42.2	2.68	68	0.1	2.5	2.76	70	1/2"	M12	730	3.24
1-1/2"	DN40	0.94	24	1.71	43.5	1/4"	M6	1.9	48.3	2.76	70	0.1	2.5	3.15	80	1/2"	M12	730	3.24
2"	DN50	0.98	25	1.79	45.5	1/4"	M6	2.37	60.3	3.23	82	0.12	3	3.54	90	1/2"	M12	730	3.24
2-1/2"	DN65	1.26	32	2.2	56	3/8"	M10	2.87	73	4.21	107	0.12	3	4.33	110	1/2"	M12	1350	6.00
2-1/2"	DN65	1.57	40	2.2	56	3/8"	M10	2.99	76	4.21	107	0.12	3	4.33	110	1/2"	M12	1350	6.00
3"	DN80	1.57	40	2.4	61	3/8"	M10	3.5	88.9	4.76	121	0.12	3	4.72	120	1/2"	M12	1350	6.00
3-1/2"	DN90	1.57	40	2.52	64	3/8"	M10	4	101.6	5.31	135	0.16	4	5.51	140	1/2"	M12	1350	6.00
4"	DN100	1.77	45	2.89	73.5	3/8"	M10	4.5	114.3	5.83	148	0.16	4	5.91	150	5/8"	M16	1430	6.36
5"	DN125	1.97	50	3.52	89.5	1/2"	M12	5.56	141.3	7.2	183	0.2	5	7.09	180	5/8"	M16	1430	6.36
6"	DN150	1.97	50	3.5	89	1/2"	M12	6.63	168.3	8.54	217	0.2	5	8.66	220	3/4"	M20	1940	8.63
8"	DN200	2.24	57	4.09	104	5/8"	M16	8.63	219.1	10.83	275	0.2	5	11.02	280	3/4"	M20	2000	8.89
10"	DN250	2.24	57	4.55	115.5	5/8"	M16	10.75	273	13.35	339	0.24	6	13.39	340	7/8"	M22	3600	16.00
12"	DN300	2.24	57	4.7	119.5	3/4"	M18	12.75	323.9	15.31	389	0.24	6	14.96	380	7/8"	M22	3800	16.90

