

## UTT 40 Loop Hanger

# Pipe Hangers

**Function:** Recommended for suspension of non-insulated stationary pipe line.

**Size:** 1/2" Thru 12"

**Material:** Carbon steel

**Finish:** Black Painted or Galvanized



| Size   |       | A     |       | D     |       | T    |     | F1   |      | F2   |      | RS   |     | Max. Rec. Load |       |
|--------|-------|-------|-------|-------|-------|------|-----|------|------|------|------|------|-----|----------------|-------|
| in     | mm    | in    | mm    | in    | mm    | in   | mm  | in   | mm   | in   | mm   | in   | mm  | lbs            | KN    |
| 1/2"   | DN15  | 1.69  | 41.5  | 0.87  | 21.3  | 0.05 | 1.2 | 1    | 24.5 | 1    | 24.5 | 3/8" | M10 | 300            | 1.334 |
| 3/4"   | DN20  | 1.85  | 45.3  | 1.09  | 26.7  | 0.05 | 1.2 | 1    | 24.5 | 1    | 24.5 | 3/8" | M10 | 300            | 1.334 |
| 1"     | DN25  | 2.02  | 49.5  | 1.36  | 33.4  | 0.05 | 1.2 | 1.06 | 26   | 1.06 | 26   | 3/8" | M10 | 300            | 1.334 |
| 1-1/4" | DN32  | 2.21  | 54.2  | 1.72  | 42.2  | 0.05 | 1.2 | 1.06 | 26   | 1.06 | 26   | 3/8" | M10 | 300            | 1.334 |
| 1-1/2" | DN40  | 2.31  | 56.5  | 1.97  | 48.3  | 0.05 | 1.2 | 1.06 | 26   | 1.06 | 26   | 3/8" | M10 | 300            | 1.334 |
| 2"     | DN50  | 2.54  | 62.2  | 2.46  | 60.3  | 0.05 | 1.2 | 1.06 | 26   | 1.06 | 26   | 3/8" | M10 | 300            | 1.334 |
| 2-1/2" | DN65  | 3.79  | 92.9  | 2.98  | 73    | 0.08 | 2.0 | 1.1  | 26   | 1.06 | 26   | 3/8" | M10 | 525            | 2.334 |
| 3"     | DN80  | 4.1   | 100.5 | 3.63  | 88.9  | 0.08 | 2.0 | 1.1  | 26   | 1.06 | 26   | 3/8" | M10 | 525            | 2.334 |
| 3-1/2" | DN90  | 4.1   | 100.5 | 4.15  | 101.6 | 0.08 | 2.0 | 1.1  | 26   | 1.06 | 26   | 3/8" | M10 | 585            | 2.600 |
| 4"     | DN100 | 4.63  | 113.4 | 4.67  | 114.3 | 0.08 | 2.0 | 1.1  | 26   | 1.06 | 26   | 3/8" | M10 | 650            | 2.890 |
| 5"     | DN125 | 5.54  | 135.7 | 5.77  | 141.3 | 0.12 | 3.0 | 1.3  | 31   | 1.27 | 31   | 1/2" | M12 | 1000           | 4.445 |
| 6"     | DN150 | 6.29  | 154.1 | 6.87  | 168.3 | 0.12 | 3.0 | 1.3  | 31   | 1.27 | 31   | 1/2" | M12 | 1000           | 4.445 |
| 8"     | DN200 | 7.85  | 192.4 | 8.94  | 219.1 | 0.12 | 3.0 | 1.3  | 31   | 1.27 | 31   | 1/2" | M12 | 1000           | 4.445 |
| 10"    | DN250 | 9.63  | 236   | 11.14 | 273   | 0.2  | 5.0 | 1.6  | 40   | 1.63 | 40   | 5/8" | M16 | 1000           | 4.445 |
| 12"    | DN300 | 11.51 | 282   | 13.22 | 323.9 | 0.2  | 5.0 | 1.6  | 40   | 1.63 | 40   | 5/8" | M16 | 1000           | 4.445 |

